

**WINCOR**  
**NIXDORF** ProCash 2100xe

Automated  
Teller Machine



*Advanced function lobby  
ATM for indoors*

FEATURES INCLUDE:

- Frontload or rearload
- Standard PC with Pentium IV
- Output of bundles of up to 60 notes
- LCD (12.1" or 15") with autoscaling function
- Different installation variants with ready-made frames
- EMV 2000-certified
- Optical indicators at all input and output modules

Options:

- custom colors
- labeling in Braille
- energy-saving function

Available with:

- Automated bulk cash and check deposit  
- CCDM (Cash/Check Deposit Module)

**The ProCash 2100xe offers a variety of functions coupled with a design that meets demanding ergonomic requirements. This system adapts ideally to a financial institution's functional requirements. This flexibility also applies to the varied installation options: freestanding or built-in system, half through the wall or integrated completely with a frame.**

In addition to its basic functions of dispensing cash and displaying information, the ProCash 2100xe can be configured to meet a financial institution's specific requirements.

- Load/unload electronic purse
- Print receipts or other documents with a full-graphics printer
- Issue tickets or vouchers from versatile cassettes
- Audio systems (loudspeakers/headset)

Powered by:



Phone: (800)572-1416 Ext. 102

Fax: (610)924-0317

Email: [mike.everhart@bardbusiness.com](mailto:mike.everhart@bardbusiness.com)

# **WINCOR NIXDORF** ProCash 2100xe

## **TECHNICAL DATA**

### **SYSTEM CONTROL**

Standard PC

### **DISPLAY**

The various VGA, SVGA and XGA resolutions can be implemented on a single display due to the autoscaling function.

- 12.1" TFT LCD
- 15" TFT LCD

### **OPTIONS**

- Touch screen
- Sichtschutzfilter
- Sunlight readable screen

### **KEYBOARD**

- 8 softkeys made of stainless steel
- Numeric keypad including 4 function keys

### **KEYBOARD OPTIONS**

- Encrypting PIN Pad (EPP)
- Encryption/decryption module (EDM)
- Keyboard privacy screen
- Alphanumeric keyboard
- Labeling in Braille

### **ELECTRONIC PURSE**

- Loading and unloading of electronic purses (transaction module for the German GeldKarte)

### **CARD HANDLING**

- Hybrid card reader (motorized)
- EMV 2000-certified
- Tamperproof card slot
- Card retained if not removed, returned in case of power failure

### **CARD HANDLING OPTIONS**

- DIP reader
- DIP hybrid reader
- CIM 86 and/or MM preparation
- Different card retract boxes

### **CASH DISPENSING**

- 1 to 4 cassettes (sealable as standard)
- Max. filling height per cassette: 310 mm
- Single reject/bundle retract, storage in separate compartments

### **CASH DISPENSING OPTIONS**

- Cassette with lock
- Cassette with low cash sensor
- Cassette pre-setting

## **SECURITY**

### **SAFES**

- UL 291 Level 1
- CEN III / VdS / CNPP
- CEN IV / VdS / LGAI

## **SECURITY OPTIONS**

- Intruder alarm system
- Portrait camera
- Uninterruptible power supply

## **OPTIONS**

### **PRINTERS**

- Receipt printer (dot matrix or thermal)
- Journal printer (dot matrix or thermal)
- Statement printer (dot matrix or thermal)

### **PASSBOOK PROCESSING**

- Passbooks with a vertical fold
- Reading (ZeKoSa) and page-turn function, last line finding
- Optional retract and/or collector box for passbooks or loose sheets

### **BARCODE READER**

- Scanning and processing barcodes in various formats

### **ENVELOPE DEPOSIT**

- Integrated envelope dispenser
- Single line printing of transaction data
- Capacity: up to 200 or 300 envelopes, depending on the deposit box, special security box as an option

### **CASH/CHECK DEPOSIT MODULE**

- Cash Deposits
  - 1 or 2 cash cassettes each with a capacity of 2000 bills
  - Number of bills per bundle: 50
  - Separate compartment for counterfeit bills
- Check Processing
  - Scanning module for check bundle
  - 1 or 2 check cassettes each with a capacity of 2000 checks
  - Number of checks per bundle: 50

### **MISCELLANEOUS**

- Lighted logo area
- Info panel for card symbols
- Loud speakers and/or headset
- Bag rest

### **OPERATING SYSTEM**

- Windows NT
- Windows XP

### **APPLICATION SOFTWARE**

- ProClassic
- IBM 473x/PBM Emulation
- NDC (NCR Direct Connect)
- DDC (Diebold Direct Connect)

### **POWER SUPPLY**

110 - 120V~/220 - 240V~, 50-60 Hz

### **ENVIRONMENTAL**

Temperature: +5°C to +40°C  
Relative humidity: 5% to 85%