

WINCOR NIXDORF ProCash 2250xe

Automated Teller Machine



Advanced function ATM for outdoors...drive-up model

FEATURES INCLUDE:

- Rearload system, through-the-wall installation
- Compact size
- Standard PC with Pentium IV
- Output of bundles of up to 60 notes
- Sunlight LCD (12.1") with autoscaling function
- Climate control unit for installation outdoors
- EMV 2000-certified
- Optical indicators at all input and output modules

Options:

- advertising attachment
- custom colors
- logo lighting
- labeling in braille

Available with:

- Automated bulk cash and check deposit
- CCDM (Cash/Check Deposit Module)

The ProCash 2250xe has been developed specifically for use from cars. A climate control unit that is available as an option ensures availability even in the harshest weather conditions. This system can be installed at locations where space is limited.

In addition to its basic functions of dispensing cash and displaying information, the ProCash 2250xe can be extended to meet a financial institution's specific requirements.

- Load/unload electronic purse
- Print receipts or other documents with a full-graphics printer
- Issue tickets or vouchers from versatile cassettes

Powered by:



Phone: (800)572-1416 Ext. 102

Fax: (610)924-0317

Email: mike.everhart@bardbusiness.com

WINCOR NIXDORF ProCash 2250xe

TECHNICAL DATA

SYSTEM CONTROL

Standard PC

DISPLAY

The various VGA, SVGA and XGA resolutions can be implemented on a single display thanks to the autoscaling function.

- 12.1" TFT LCD sunlight

OPTIONS

- Touch screen
- Privacy display filter

KEYBOARD

- 8 stainless steel softkeys
- Numeric keypad including 4 function keys

OPTIONS

- Encrypting PIN pad (EPP)
- Encryption/decryption module (EDM)
- Braille labeling

ELECTRONIC PURSE

- Loading and unloading of electronic purses (transaction module for the German GeldKarte)

CARD HANDLING

- Hybrid card reader (motorized)
- EMV 2000-certified
- Tamperproof card slot
- Card retained if not removed, returned in case of power failure

OPTIONS

- CIM 86 and/or MM (preparation)
- Different card retract boxes

CASH DISPENSING

- 1 to 4 cassettes (sealable as standard)
- Max. filling height per cassette: 310 mm/12,20 in.
- Single reject/bundle retract, storage in separate compartments

OPTIONS

- Cassette with lock
- Cassette with low cash sensor
- Cassette pre-setting

SECURITY

SAFES

- UL 291 Level 1

OPTIONS

- Intruder alarm system
- Portrait camera
- Uninterruptible power supply

OPTIONS

PRINTERS

- Receipt printer (dot matrix or thermal)
- Journal printer (dot matrix or thermal)
- Statement printer (dot matrix or thermal)

ENVELOPE DEPOSIT

- Integrated envelope dispenser
- Single line printing of transaction data
- Capacity: up to 200 or 300 envelopes, depending on the deposit box, special security box as an option

CASH/CHECK DEPOSIT MODULE

- Cash Deposits
 - 1 or 2 cash cassettes each with a capacity of 2000 bills
 - Number of bills per bundle: 50
 - Separate compartment for counterfeit bills
- Check Processing
 - Scanning module for check bundle
 - 1 or 2 check cassettes each with a capacity of 2000 checks
 - Number of checks per bundle: 50

MISCELLANEOUS

- Lighted logo area
- Info panel for card symbols
- Loud speakers and/or headset
- Climate control unit (heating)

OPERATING SYSTEM

- Windows NT
- Windows XP

APPLICATION SOFTWARE

- ProClassic
- IBM 473x/PBM Emulation
- NDC (NCR Direct Connect)
- DDC (Diebold Direct Connect)

POWER SUPPLY

110 - 120V~/220 - 240V~, 50-60 Hz

ENVIRONMENTAL

- Without climate control unit:
 - Temperature: +5° C to +40° C (+41° F to +104° C)
- With climate control unit:
 - Temperature: - 40° C to +50° C (-40° F to +122° F)(Customer panel)
- Relative humidity: 5% to 85%