

WINCOR NIXDORF ProCash 2350xe

Automated Teller Machine



*Advanced function ATM for outdoor use
Free-standing island drive-up system*

FEATURES INCLUDE:

- Made of highly specialized durable materials with a universal UL-listed acrylic-coated housing
- Climate control unit includes air conditioning as standard
- Frontload system with modular design for ease and speed of serviceability
- Fits standard 42" islands
- Individual color customization option supports individual branding
- Standard equipment includes Pentium PC
- 12.1" sunlight-readable LCD screen with autoscaling functionality
- Issues bundles of up to 60 banknotes
- Lighted indicators at all input and output modules,
- Labeling in Braille

Available with:

- Automated bulk cash and check deposit
- CCDM (Cash/Check Deposit Module)

Designed especially for operation from the secure and comfortable environment of a car, the ProCash 2350xe guarantees 24/7 hour service even in the most rugged environments. The ergonomic layout of all its elements allows easy use from all kinds of vehicles.

The ProCash 2350xe has a modular design and is easy and fast to service – critical requirements especially for outdoor drive-up installations. Highly specialized durable materials ensure that the ProCash 2350xe will withstand vandalism and all forms of climate conditions.

The ProCash 2350xe is a full function, free-standing frontload system. Its climate control unit and rugged design make the ProCash 2350xe ideal for harsh outdoor environments.

In addition to its basic functions of dispensing cash and displaying information, the ProCash 2350xe can be enhanced to meet a financial institution's specific requirements:

- Load/unload electronic purse
- Print receipts or other documents with a full-graphics printer
- Issue tickets or vouchers from versatile cassettes

Powered by:



Phone: (800)572-1416 Ext. 102

Fax: (610)924-0317

Email: mike.everhart@bardbusiness.com

WINCOR NIXDORF ProCash 2350xe

TECHNICAL DATA

SYSTEM CONTROL

Standard PC

DISPLAY

The various VGA, SVGA and XGA resolutions can be implemented on a single display due to the autoscaling function.

- 12.1" TFT LCD

DISPLAY OPTIONS

- Touch screen
- Privacy display filter

KEYBOARD

- 8 softkeys made of stainless steel
- Numeric keypad including 4 function keys

KEYBOARD OPTIONS

- Encrypting PIN pad (EPP)
- Encryption/decryption module (EDM)

CARD HANDLING

- Hybrid card reader (motorized)
- EMV 2000-certified
- Tamperproof card slot
- Card retained if not removed
- Card returned in case of power failure

CARD HANDLING OPTIONS

- Different card retract boxes

CASH DISPENSING

- 1 to 4 cassettes (sealable as standard)
- Max. filling height per cassette: 12.20" (310 mm)
- Single reject/bundle retract, storage in separate compartments

CASH DISPENSING OPTIONS

- Cassette with lock
- Cassette with low cash sensor
- Cassette pre-setting

SECURITY

- Safe UL 291 Level 1

SECURITY OPTIONS

- Intruder alarm system
- Portrait camera
- Uninterruptible power suppl

OPTIONS

PRINTERS

- Receipt printer (dot matrix or thermal)
- Journal printer (dot matrix or thermal)
- Statement/information printer (dot matrix or thermal)

ENVELOPE DEPOSIT

- Integrated envelope dispenser
- Single line printing of transaction data
- Capacity: up to 200 or 300 envelopes, depending on the deposit box, special security box as an option

CASH/CHECK DEPOSIT MODULE

- Cash Deposits
 - 1 or 2 cash cassettes each with a capacity of 2000 bills
 - Number of bills per bundle: 50
 - Separate compartment for counterfeit bills
- Check Processing
 - Scanning module for check bundle
 - 1 or 2 check cassettes each with a capacity of 2000 checks
 - Number of checks per bundle: 50

MISCELLANEOUS

- Lighted logo area
- Lighted indicators at all input and output modules
- Info panel for card symbols
- Audio functionality, headset plug
- Climate control unit, air conditioning as standard

OPERATING SYSTEM

- Windows NT
- Windows XP

APPLICATION SOFTWARE

- ProClassic
- IBM 473x/PBM Emulation
- NDC (NCR Direct Connect)
- DDC (Diebold Direct Connect)

POWER SUPPLY

110 - 120V~/220 - 240V~, 50-60 Hz

ENVIRONMENTAL

- Temperature range: --30° F to 122° F (-35° C to 50° C)
- Relative humidity: 5% to 85%